



**ONE WORLD  
TOUCH**  
TOUCH SCREEN SOLUTIONS

# 32" Multi-Touch Display (LM-3234-39E Model)

- Full 1080p Resolution (1920 x 1080)
- Projected Capacitive Multi-Touch
- OPS Expansion Slot for Internal PC
- Internal Speakers
- 3 Year Limited Warranty



## Product Specifications:

<b>Size/Type</b>	32 inch Diagonal/ S-IPS LCD Panel & LED Backlit	
<b>Touch Technology</b>	Projected Capacitive (up to 10 Touch Points with Win 7/8)	
<b>Resolution</b>	1920 x 1080	
<b>Brightness</b>	450 cd/m2	
<b>Audio</b>	Built-in speakers, & optional external speakers	
<b>Contents of Packaging</b>	User's Manual, Power Cord, Wireless Remote, Batteries, DVI-D Cable Setup Sheet & Driver CD	
<b>Contrast Ratio</b>	1300:1	
<b>Dimensions</b>	Net (with stand) - (WxHxD) 29.5 x 19.6 x 9.4 in./750 x 497.1 x 240mm Net (without stand) 29.5 x 17.5 x 2.4 in./750 x 444.5 x 60.8mm	
<b>Input Signal</b>	Video: ANALOG RGB Vp-p/75 Ohms Digital TMDS / DisplayPort Sync: Separate sync: TTL Level (Positive/Negative)	
<b>Input</b>	<b>Digital</b> -	HDMI, DVI-D, DisplayPort
	<b>Analog</b> -	VGA 15-pin D-sub (shared S-Video, Video, Component, RGB)
	<b>Audio</b> -	Stereo Mini-Jack, HDMI Audio, DisplayPort Audio
	<b>External Control</b> -	RS-232C, Ethernet (RJ45), IR Remote
<b>Output</b>	<b>Audio</b> -	Stereo Mini-Jack
	<b>Digital</b> -	DVI-D
<b>Limited Warranty</b>	3 Years Parts and Labor Including Backlight	
<b>Operating Humidity</b>	20-80%	
<b>Operating Temperature</b>	5-40° C/41-104° F	
<b>Storage Humidity</b>	10-90%	
<b>Storage Temperature</b>	-20-60° C/-4-140° F	
<b>Pixels Pitch</b>	0.36mm	
<b>Power Consumption</b>	(typical) On: 48W / Power Savings Mode: <1W	
<b>Synchronization Range</b>	Horizontal: Analog: 15.625 / 15.734 / 31.5 - 91.1 KHz, Digital: 31.5 - 91.1KHz Vertical: 50-85 Hz Analog / 50-85 Hz Digital	
<b>VESA Hole Configuration Spec.</b>	200 x 200mm (4 hole)	
<b>Viewing Angle</b>	178° Vert. 178° Hor. (89U/89D/89L/89R)@ CR>10	
<b>Weight</b>	(with stand) 25.0 lbs./11.4 kg / (without stand) 23.8 lbs./10.8 kg	
<b>Additional Features</b>	Ethernet Controllable, TileMatrix (10x10), TileComp, PIP/POP/Side by side picture, 6-axis color adjustment, 10-bit gamma, programmable zoom, scheduler, off-timer (countdown), screen saver, vacation switch, AutoBright, portrait mode capable, color temperature adjust	