



19" LED Backlit Touch Monitor (DM-1900-05C Model)

- Using NEC Model AS194Mi-BK
- Resistive, Capacitive or PCAP Touch
- LED Backlit - Low Power Consumption
- 3 Year Limited Warranty



Product Specifications:

Size/Type	19 inch Diagonal/ IPS LCD Panel with LED Backlight
Touch Technology	Resistive or Capacitive (Single Touch), Projected Capacitive (Multi-Touch)
Brightness	250 cd/m ²
Contents of Packaging	User's Manual, Power Cord, Video Cable(s), Setup Sheet & Driver CD
Contrast Ratio	1000:1
Aspect Ratio	5:4
Resolution	1280 x 1024
Pixels Per Inch	87
Power Consumption	On: 14W / Power saving mode: 0.3W
Viewing Angle	178 Degree Vertical, 178 Degree Horizontal
Dimensions (W x H x D)	With Stand: 16.2 x 15.9 x 8.1 in. / 412.5 x 403.1 x 205.1 mm Without stand: 16.2 x 13.4 x 2.7 in. / 412.5 x 341.2 x 69 mm
Display Colors	More than 16.7 million
Input Video Signal	ANALOG: 0.7 Vp-p/75 Ohms
Input	DisplayPort, HDMI and VGA 15 pin D-sub
Limited Warranty	3 Years Parts and Labor including Backlight
Operating Altitude	2000m / 6,562 ft.
Operating Humidity	20-80%
Operating Temperature	5-35°C / 41-95°F
Storage Altitude	12,192m / 40,000 ft.
Storage Humidity	10-85%
Storage Temperature	-10-60°C / 14-140°F
Sync	Separate Sync: TTL Level (positive/negative)
Synchronization Range (Automatic)	Horizontal: 31.5 kHz to 81 kHz (Analog/Digital) Vertical: 56 Hz to 76 Hz
VESA Hole Configuration Spec.	100mm x 100mm
Voltage Rating	100-240V @ 50/60Hz
Weight	Net: 8.6 lbs. / 3.9 kg / Net (without stand): 7.5 lbs. / 3.4 kg
Additional Features	Tilt, No Touch Auto Adjust, cable management,, NaViSet software, digital smoothing, digital controls, user (OSD) controls, AccuColor color control, DDC/CI, VESA DPMS power management, ISO 13406-2 Class II
Response Time (typical)	Rapid Response (5ms)