



## 32" 4K Multi-Touch Display (LM-3237-26-4K Model)



- **10 Point PCAP Multi-Touch**
- **3840 x 2160 4K Resolution**
- **Flat Front Surface Design**
- **3 Year Warranty**

### Product Specifications:

<b>Size/Type</b>	32 inch Diagonal/LCD Display
<b>Touch Technology</b>	Projected Capacitive 10 Point Multi-Touch
<b>Surface Durability</b>	Mohs' 7H
<b>Brightness</b>	350 cd/m2 (Nits)
<b>Contents of Packaging</b>	AC Adapter, AC Power cord/ USB Touch Cable
<b>Contrast Ratio</b>	3000:1
<b>Aspect Ratio</b>	16:9
<b>Colors</b>	more than 1 billion (depending on video card used)
<b>Response Time</b>	9.5 ms Typical
<b>Active Area</b>	27.49" (W) x 15.46" (H) / 698.4 (W) x 392.85 (H) mm
<b>Dimensions</b>	30.65" (W) x 18.64" (H) x 1.96" (D) / 778.7 x 473.6 x 50 mm
<b>Weight</b>	Monitor: 27 lbs / 12.2 kg Shipping: 39 lbs / 17.7 kg
<b>Input</b>	HDMI, DVI-D & DisplayPort
<b>Limited Warranty</b>	3 year including backlight
<b>Operating Temperature</b>	32-104 F / 0-40 C
<b>Operating Humidity</b>	20% - 80%
<b>Pixel Pitch</b>	0.181 x 0.181mm
<b>Resolution</b>	3840 x 2160
<b>Storage Altitude</b>	40,000 ft. / 12,192m
<b>Storage Humidity</b>	5%-90%
<b>Storage Temperature</b>	-20-60 C/-4-140 F
<b>VESA Hole Configuration Spec.</b>	200 x 200 mm (4 hole x M4)
<b>Viewing Angle</b>	178° Vert., 178° Hor. (89U/89D/89L/89R)
<b>Input Voltage</b>	12V DC +/- 5%
<b>Voltage Rating</b>	AC 100-240V, 50/60Hz
<b>Orientation</b>	Landscape or Portrait supported